

The Micergy M-Power series is a high-performance, scalable battery energy storage system designed for residential power back-up and off-grid scenarios, thanks to the built-in smart BMS, it allows up to 15 units in parallel connection to meet tailored power needs, besides, it provides the protection and recovery functions of overvoltage, undervoltage, overcurrent, high temperature, low temperature, short circuit and charging reverse connection. Realize the SOC precise measurement and SOH health status statistics in the process of charging and discharging, now enjoy the safety power with M-Power.



High Flexibility.

Up to 15 pcs in parallel, scalable from 14.33kWh to 215.4kWh.



Wide Compatibility.

Matching with leading battery inverters.




Easy maintenance.

Cell level replacement simple by bolt and nut connection



APP monitoring(Optional).

Real-time monitoring by Bluetooth or WiFi



Compact sleek
streamline design



Blade Cell, Super
Thin Design



Long lifespan,
8000 cycles




User-friendly, 2.8"
touch screen



CAN/RS485
Communication

GENERAL SPECIFICATIONS	Model		CB-280
Electrical Performance	Nominal Energy		14.33kWh
	Nominal Voltage		51.2V
	Nominal Capacity		280Ah
	Operating Voltage Range		44.8V-58.4V
	Cycling Performance		>8000 Cycle @ 0.5C, 25°C, 70%EOL
Operating Parameters	Maximum Charging Current(A)		200A
	Maximum Discharging Current(A)		200A
	Charging Cut-off Voltage(V)		44.8V
	Discharge Cut-off Voltage(V)		58.4V
	Recommended Charging Current(A)		100A
	Recommended Discharging Current(A)		100A
	Humidity		0-95%
	Altitude		≤2000m
	Charging Temperature		0°C-65°C
	Discharging Temperature		-20°C-65°C
	Storage Temperature		-20°C-45°C, SOC:20%-50%
Physical Parameters	Product Dimension(W*H*D, mm)		647.7*1181.1*381
	Gross Weight		135kg
	Ingress Protection Protection		IP20
	Installation		Standing
Communication	Communication	Standard(CAN, RS485), Optional(Bluetooth, WiFi)	
	Compatible Inverter Brand	Deye, Pylon, Voltronic, Growatt, SRNE, Luxpower, Goodwe etc...	
	Display	2.8" Touch Screen, LED Indicators	
	Scalability	Max. 15pcs in Parallel with Automatic Addressing Function	
Warranty	Warranty	10 Years	
	Design Performance Life	20 Years	



* System Usable Energy may vary with different Inverter.

* Charging and discharging performance may vary with Temperature and SOC.

Micergy

Micergy Company Limited

Address: Building No.88, Liangtouwei Road, Qingxi Town, Dongguan City, Guangdong Province, China
Email: info@micergy.com ; Website: www.micergy.com

The Micergy word mark and logo are registered trade marks owned by Micergy Company Limited and its Subsidiaries.
All features, functionality and other product specifications are subject to change without notice or obligation.
© 2024 Micergy Co., Ltd. All rights reserved.

